



Quality Seed And Grain Equipment

Medium Size Air Screen Cleaner



- Pre & Post Air System (2-Air) with “HIGH” Static Fans – Standard
- Independent Motors for the Fan, Eccentric & Feed-Roll
- Adjustable Screen Shake Speed by the use of a VFD on Eccentric Motor
- Direct Drive Feed-Roll to provide precision control of Feed by the use of a VFD
- TEFC, NEMA Premium Efficient Motors; X-Proof Available
- Easy access to screens for clean-out and screen changes
- Heavy Duty Eccentric Assembly, all components are CNC Machined
- Precision Fan Damper Controls
- Hopper Options:
 - Trashy Product Hopper with additional “Mixer” Shaft
 - Vibratory Hopper for gentle handling & precision control

Other Options: X-Proof Motors, 50 Hz Motors, Higher Capacity 9° Sift, Collection/Discharge Spouting Packages, SUB-Frames, Fan Transitions & “Wye” Pants, Machine Mounted Hopper Bin, Tailored to accept Competitor Screens, Customized Machine Floor Plan, ETC.



Q-SAGE Medium Size Air/Screen Cleaners

Q-SAGE Model	Machine Flow Scalp + Sift	Screen Size & QTY				Cleaning Capacity-Based on Wheat (BPH)
		QTY	Width	Length	Screen Area (Sq. Ft.)	
3x60-42	1+2	3	42"	60"	52.5	125-175
3x60-54	1+2	3	54"	60"	67.5	160-250
3x72-54	1+2	3	54"	72"	81	200-350
3x88-54	1+2	3	54"	88"	99	225-400
4x60-42	2+2 or 1+3	4	42"	60"	70	125-200
4x60-54	2+2 or 1+3	4	54"	60"	90	160-250
5x60-42	2+1+2 or 2+3 or 1+4	5	42"	60"	88	125-200
5x60-54	2+1+2 or 2+3 or 1+4	5	54"	60"	113	160-250
6x60-42	1+2+1+2 or 1+2+3 or 2+4	6	42"	60"	105	190-300
6x60-54	1+2+1+2 or 1+2+3 or 2+4	6	54"	60"	135	225-400
4x72-54	2+2 or 1+3	4	54"	72"	108	190-300
5x72-54	2+1+2 or 2+3	5	54"	72"	135	225-400
4x88-54	2+2 or 1+3	4	54"	88"	132	225-400

